

In the Specification

Please amend the specification of this application as follows:

Rewrite the paragraph at page 7, line 16 to page 8, line 5 as follows:

--In microprocessor 1 there are shown a central processing unit (CPU) 10, data memory 22, program memory 23, peripherals 60 and an external memory interface (EMIF) with a direct memory access (DMA) 61. CPU 10 further has an instruction fetch/decode unit 10a-c, a plurality of execution units, including an arithmetic and load/store unit D1, a multiplier M1, an ALU/shifter unit S1, an arithmetic logic unit ("ALU") L1, a shared multi-port register file 20a from which data are read and to which data are written. Decoded instructions are provided from the instruction fetch/decode unit 10a-c to the functional units D1, M1, S1, and L1 over various sets of control lines which are not shown. Data are provided to/from the register file 20a from/to the load/store unit D1 over a first set of busses 32a, to multiplier M1 over a second set of busses 34a, to ALU/shifter unit S1 over a third set of busses 36a and to ALU L1 over a fourth set of busses 38a. Data are provided to/from the memory 22 from/to the load/store unit D1 via a fifth set of busses 40a. Note that the entire data path described above is duplicated with register file 20b and execution units D2, M2, S2, and L2. Load/store unit D2 similarly interfaces with memory 22 via a set of busses 40b. Instructions are fetched by fetch unit 10a from instruction memory 23 over a set of busses 41. Emulation circuitry 50 provides access to the internal operation of integrated circuit 1 which can be controlled by an external test/development system (XDS) 51. Peripherals 60 connect to external peripherals ~~80~~ 82 via bus 80. CPU 10 also includes interrupt controller 90, control logic 100 and configuration registers 102.--